

1139.00 EUR

incl. 19% VAT, plus [shipping](#)



- INTEL® BayTrail--M N2930 SOC Chip
- Onboard INTEL® BayTrail-M N2930 1.83GHz Quad Cores CPU
- Onboard SAMSUNG 4G/1333MHz DDR3L Memory
- Support DirectX 11 3D Graphics Acceleration
- Support 1*Serial ATAll(3Gb/s) Devices
- Support Dual INTEL® Gigabit LAN
- Support CRT Output
- Equipped with 802.11 b/g/n WIFI card & External Antenna
- Support 3* COM ports■COM2/COM3 Support RS422/485■
- Support 2.5" SATA HDD
- Support 1*M-SATA Socket
- Support 1*Mini PCI-E Socket
- Support 3* USB2.0 Ports
- Support 1* USB3.0 Port
- Support 3G SIM Card
- Support slick design, IP65 Rating
- VESA mount(100mm X100mm &75mm x 75mm)

Panel	Panel Spec	AUO G170ETN01.0
	Viewable Size Image	17.0 inch With LED Backlight
	Active Area	337.920(H) x 270.336(V)
	Resolution	1280 x 1024 @60Hz
	Display Color	16.7M
	Pixel Pitch	0.264 x 0.264 mm
	Aspect Ratio	4:3
	Contrast Ratio	1000:1
	Max Brightness	350 cd/m ²
	Viewing Angle(H/V)	H170/V160
	Response Time	3.5ms
	Temperature Range	0 ■ +50■(Operating)

Touch	Touch panel style	5 wires analog resistive
	Active Range	337.00 x 269.50mm ±0.2mm
	Temperature Range	-10 ~ +60 (Operating)
	Transparency	80 ±3%
	Surface Hardness	3H (ASTM D3363, pressure 750g/45°)
	Operating Force	80g
	Knock test	10,000,000 times keystrokes