



98.00 EUR  
 incl. 19% VAT, plus [shipping](#)

9-Port Fast Ethernet Switch with 8-Port PoE provides the seamless network connection. It integrates 10/100Mbps Fast Ethernet network capabilities.

9 Auto-Negotiation RJ45 ports (port-1 to port-8) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

**Easy To Use**

Easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the 9-Port Desktop Switch with 8-Port PoE is a great selection for expanding your home or office network.

**Key Features:**

- \* Supports PoE power up to 15.4W for each PoE port
- \* Supports PoE power up to 60W for all PoE ports
- \* Supports PoE IEEE 802.3af compliant PDs
- \* Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- \* 8 ports with poe, 1 port 10/100 RJ45
- \* SmartLink intelligent power management
- \* One key Standard Switch/VLAN-Isolation(MTU VLAN)
- \* External power adapter (96W[52V/1.85A])

Interface	9x 10/100Mbps RJ45 Ports 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
Network Media	EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
External Power Supply	External Power Adapter(Output: 48VDC /1.25A) Standard: 802.3 af/at compliant
PoE Ports (RJ45)	PoE Ports: Port1- Port 8 Power Supply: 96W
Backbound Bandwidth	1Gbps
Mac Address Table	2K
Dimensions ( W x D x H )	217mm(L) * 105mm(W) *28mm(H)
Transmission Method	Store-And-Forward

Advanced Functions

Compatible With IEEE 802.3af Compliant PDs Priority Function  
IEEE802.3x Flow Control full-duplex and Backpressure half-duplex  
IEEE802.3az EEE

Certification

LED indicators for POE, Link, Activity, Speed  
CE, FCC, RoHS

Package Contents

Switch, Power Adapter  
Operating Temperature: -10°C~55°C

Environment

Storage Temperature: -20°C~60°C  
Operating Humidity: 10% ~ 90% non-condensing  
Storage Humidity: 5%~95% non-condensing